

# **FACILITY & EQUIPMENT**

# FACILITY

- 10.5-acre paved site (fenced yard) .
- 10,000 ft<sup>2</sup> Office ٠
- 100,000 ft<sup>2</sup> Fabrication Area, ٠
  - 50,000 ft<sup>2</sup>, multiple bays with 22 ft under hook 0
  - 45,000 ft<sup>2</sup>, large fabrication bay,100 ft x 450 ft with 30 ft under hook 0
  - 5,000 ft<sup>2</sup>, assembly bay, 50 ft x 100 ft with 55 ft under hook 0



# **CRANES**

- (2) 40-ton x 100 ft span double trolley bridge crane, 30 ft under crane hook large fabrication bay ٠
- (2) 15-Metric ton bridge cranes, 55 ft under crane hook assembly bay .
- **\*** (1) 15-ton side gantry crane – large fabrication bay
- (4) 5-ton side gantry crane large fabrication bay
  (3) 10-ton bridge crane, 22 ft under crane hook ٠
- ٠
- ٠ (4) 5-ton bridge crane, 22 ft under crane hook
- (30+) 1-ton ~ 7.5-ton jib crane .

## FORKLIFTS

- Yale, 32,000 lb. ٠
- CombiLift, 17,000 lb. Multidirectional ÷
- ÷ Toyota, 8,550 lb.
- (2) Toyota, 5,000 lb. ٠
- ••• Yale, 5,000 lb.

## **FABRICATION SUPPORT**

- ÷ Multiple, linear and radial, precision floor imbeds in large fab bay, configurable fixturing up to 90 ft long.
- . Inlaid track for movement of heavy product within fabrication bays and extending outside of shop.
- Numerous welding positioners up to 40,000 lb. capacity Numerous turning rolls up to 40-ton capacity **\***
- ÷
- $\dot{\mathbf{v}}$ Large number of hand tools, tooling, benders, material handling, etc.
- \* Dedicated stainless steel fabrication bay for mitigation of cross contamination

#### **PRESS BRAKES**

- Accura Press, CNC, 3-axis, 320-ton x 12 ft ٠
- ٠ DiAcro, Manual, 15-ton x 4 ft

#### ROLLS

- Roundo, Plate Roll, 4-roll double I.P. CNC, 12' x 1-5/8" ÷
- Roundo, Plate Roll, 4-roll double I.P. CNC, 10' x 9/16" ٠
- Roundo, Plate Roll, 3-roll double I.P., 10' x 5/8" .
- ٠ Montgomery, Plate Roll, 4-roll double I.P., 6' x 1/4"
- Roundo, Angle Roll R5, L41/2 x 41/2 x 1/2" Capacity ٠
- \*\* DiAcro, 2-roll urethane pinch, 16" x 3/16"

#### PLATE CUTTING - LASER / OXY / PLASMA

- Mazak Optiplex 4020, 4 kw, 78" x 157" travel, shuttle table \*
- ٠ Kinetic 4000 cutting system, 8' x 20' table
  - 260-amp high-definition plasma 0
  - Plasma bevel head 0
  - Oxy fuel head 0
  - 0 24 station machining head - drilling, tapping, chamfering
- Kinetic 2500 cutting system, 10' x 24' table •
  - 260-amp high-definition plasma 0
  - Twin head 0

#### SHAPE CUTTING - LASER / SAW

- Mazak FabriGear, 4 kw, 6-axis with tapping, 8-5/8" OD x 26 ft
- ٠ HE&M, Automatic Feed, 24" x 24" capacity, programmable
- ٠ HYD-MECH, Vertical, 18" x 20" capacity
- ٠ HYD-MECH, Horizontal Automatic Feed, 18" x 18" capacity
- ٠ Powermatic, Vertical, 19" throat
- ••• Soco, Cold Saw, 14" Blade

#### **WELDING MACHINES**

- ٠ GTAW - (20+) various models
- GMAW/FCAW (50+) various models •••
- . SAW - Teledyne Readco, 12' x 12' track manipulator
- ٠ SAW - Ransome, 10'x10' track manipulator
- . SAW - Pandjiris, 12'x12' stationary seam welder
- ••• SAW - Pandjiris Double 8, 8' x 8' x 30' track manipulator
- $\Leftrightarrow$ SAW - Flat Seam Welder, 12' long x 1" thick
- ÷ SAW - Jet Line Seamer, 10 ft long (round), 1,000 amp
- ٠ GMAW/FCAW - BUG-O magnetic tractor welder
- GMAW/FCAW BUG-O dual head tractor T welder •••

#### LATHES

- Samsung CNC with live tool & steady rest 30" x 130" •
- ٠ Haas SL30, slant bed lathe 17" x 34" w/ Servo 800 bar feeder
- ٠ Mazak Integrex 200s, 5-Axis
- ÷ Haas TL25
- \*\* HNK CNC Vertical Boring Mill with Live Spindle
  - 78" table x 98" max swing 0 0
    - 70" under rail
  - 20 hp live spindle with tool changer 0
  - Right angle head attachment for side work 0
- Gray 60" chuck x 72" swing x 72" under head DRO \*

#### MILLS

- G&L, CNC Horizontal floor type, 360" x 96" x 48"
   10 ft square rotary infeed table
- Feeler, CNC Bridge Mill, 205" x 94" x 47"
- Right angle head, indexable
   Chevalier, CNC Bridge Mill, 162" x 101" x 39"
- Right angle head
- TOS, Horizontal Boring Mill, 137.8" x 98.4" x 63" + w25.6" (Installed 2024)
   5.1" Bar, Ram, Quill, Full 4th axis, Right angle head
- Femco, Horizontal Boring Mill, 4.33" bar 78" x 70" x 66"
- Full 4th axis
- Mazak CNC Horizontal Machine Center, 52" x 48" x 48"
- Dual pallet, Full 4th axis
- ✤ Haas VF6, 64" x 32" x 30"
  - 4<sup>th</sup> axis available
- Haas VF4SS, 50" x 20" x 25"
   4<sup>th</sup> axis available
- Manual Mills, several small machines

## PLATE BEVELING

Steelmax, DBM 50, 2" capacity

## PIPE THREADING

Rigid, 1224, 4" pipe capacity

# **IRON WORKERS**

- HMI, 70-ton, hydraulic
- Piranha P3, 50-ton, hydraulic

# **BLASTING AND PAINTING**

- Blast Cabinet
- Blast Booth, 24 ft x 20 ft x 70 ft with recovery floor and inlaid track, available spray to waste system for virgin media
- Paint Booth, Viking climate controlled, 18 ft high x 20 ft wide x 75 ft long with inlaid track
- Graco, X45 airless sprayer
- Graco, "President" 30:1 ratio airless sprayer
- Electrostatic sprayer
- Several Binks spray guns

# **INSPECTION AND EXAMINATION**

- ✤ FARO 3D Laser Tracker, 250 ft cube
- Saro Arm Platinum, 6 ft cube with leaping capability, coordinate measuring instrument
- Surface Plate, Various Gages and Measuring Instruments traceable to NIST
- Pneumatic / Hydrostatic Test Equipment up to 15,000 psi
- Bruker XRF Handheld PMI (Positive Material Identification) Analyzer, S1 Turbo
- Digital Psychrometer (humidity testing)
- Paint inspection instruments for adhesion, holiday, and thickness
- Liquid Penetrant (PT) examination
- Magnetic Particle (MT) examination
- Ultrasonic Thickness (UTT) Olympus 38DL Plus, Thickness Rage .003" 25.000" (Depending on material)
- Ultrasonic Shear Wave (UT) Sonatest Wave, Test material and welds for imperfections per AWS, ASME
- Bubble Leak Testing (BLT) Snoop and multiple gauges, internal and external testing.
- Vacuum Pump Stand
  - Roughing Pump Leybold Sogevac SV630B Single Stage, rotary vane pump (444 cfm, 6E-2 Torr / 8E-2 mBar)
  - High Vacuum Pump Leybold RUVAC WSU 2001 H Roots pump (1850 m^3, 3E-2 Torr / 4E-2 mBar)
     Ultra-High Vacuum Pump Shimadzu TMP-2003M Turbo Molecular Pump 2000 l/s [N2] 1x10-8 Pa / 7.5E-10
  - Torr / 1E-9 mBar).
- + Helium Tester, Leybold Ultratest UL 500 dry 5x10-11 to 10 mbar-l/s measurable helium leak rate w/ time constant < 1s